

PRIMAIRE D'ADHESION UV - WHITE, POUR MARQUAGE A CHAUD - UVART5000W**SAFETY DATA SHEET**

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1. Product identifier**

Product name : PRIMAIRE D'ADHESION UV - WHITE, POUR MARQUAGE A CHAUD

Product code : UVART5000W.

This MSDS is valid for all packaging of this product.

1.2. Relevant identified uses of the substance or mixture and uses advised against

SCREENPRINTING INK, PAD PRINTING INK

1.3. Details of the supplier of the safety data sheet

Registered company name : ITW CER.

Address : 85 RUE CASTELLION.01117.

OYONNAX.FRANCE.

Telephone : + 33 (0)4 74 73 26 40.

www.itwids.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.**Other emergency numbers**

Swiss emergency telephone number: 145 (Swiss Toxicological Information Centre)

SECTION 2 : HAZARDS IDENTIFICATION**2.1. Classification of the substance or mixture****In compliance with EC regulation No. 1272/2008 and its amendments.**

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements**In compliance with EC regulation No. 1272/2008 and its amendments.**

Hazard pictograms :



GHS07

Signal Word :

WARNING

Product identifiers :

EC 235-921-9

HEXAMETHYLENE DIACRYLATE

EC 278-355-8

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE

Additional labeling :

Hazard statements :

H315

Causes skin irritation.

H317

May cause an allergic skin reaction.

H319

Causes serious eye irritation.

H412

Harmful to aquatic life with long lasting effects.

PRIMAIRE D'ADHESION UV - WHITE, POUR MARQUAGE A CHAUD - UVART5000W

Precautionary statements - Prevention :

P280 Wear protective gloves/eye protection.

Precautionary statements - Response :

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	Note	%
CAS: 13048-33-4 EC: 235-921-9 REACH: 01-2119484737-22-XXXX HEXAMETHYLENE DIACRYLATE	GHS07, GHS09 Wng Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Aquatic Chronic 2, H411 Aquatic Acute 1, H400 M Acute = 1		25 <= x % < 50
CAS: 13463-67-7 EC: 236-675-5 REACH: 01-2119489379-17-XXXX DIOXYDE DE TITANE		[1]	10 <= x % < 25
CAS: 7473-98-5 EC: 231-272-0 REACH: 01-2119472306-39-0000 2-HYDROXY-2-METHYLPROPIOPHENONE	GHS07 Wng Acute Tox. 4, H302 Aquatic Chronic 3, H412		2.5 <= x % < 10
CAS: 75980-60-8 EC: 278-355-8 REACH: 01-2119972295-29-XXXX DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PH OSPHINE OXIDE	GHS09, GHS07, GHS08 Wng Skin Sens. 1, H317 Repr. 2, H361f Aquatic Chronic 2, H411	[2]	1 <= x % < 2.5

(Full text of H-phrases: see section 16)

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

PRIMAIRE D'ADHESION UV - WHITE, POUR MARQUAGE A CHAUD - UVART5000W

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

PRIMAIRE D'ADHESION UV - WHITE, POUR MARQUAGE A CHAUD - UVART5000W

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid skin and eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep the container tightly closed in a dry, well-ventilated place.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limits:**

- France (INRS - ED984 :2016) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
13463-67-7	-	10	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
13463-67-7	- ppm 4 mg/m ³	- ppm - mg/m ³			

- China (GBZ 2.1, 2007) :

CAS	TWA :	STEL :	Anm :	TWA :	STEL :	Anm :
13463-67-7	8 mg/m ³					

- Switzerland (SUVAPRO 2017) :

CAS	VME	VLE	Valeur plafond	Notations
13463-67-7	3 a mg/m ³			SSC

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE (CAS: 75980-60-8)

Final use:

Exposure method:
Potential health effects:
DNEL :

Workers.

Dermal contact.
Long term systemic effects.
1 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
3.5 mg of substance/m³

2-HYDROXY-2-METHYLPROPIOPHENONE (CAS: 7473-98-5)

Final use:

Exposure method:
Potential health effects:
DNEL :

Workers.

Dermal contact.
Short term systemic effects.
1.25 mg/kg body weight/day

Exposure method:
Potential health effects:

Dermal contact.
Long term systemic effects.

PRIMAIRE D'ADHESION UV - WHITE, POUR MARQUAGE A CHAUD - UVART5000W

DNEL : 1.25 mg/kg body weight/day

Exposure method: Inhalation.
Potential health effects: Short term systemic effects.
DNEL : 3.5 mg of substance/m3

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 3.5 mg of substance/m3

DIOXYDE DE TITANE (CAS: 13463-67-7)

Final use: **Workers.**
Exposure method: Inhalation.
Potential health effects: Long term local effects.
DNEL : 10 mg of substance/m3

Final use: **Consumers.**
Exposure method: Ingestion.
Potential health effects: Long term systemic effects.
DNEL : 700 mg/kg body weight/day

HEXAMETHYLENE DIACRYLATE (CAS: 13048-33-4)

Final use: **Workers.**
Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 2.77 mg/kg body weight/day

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 24.5 mg of substance/m3

Final use: **Consumers.**
Exposure method: Ingestion.
Potential health effects: Long term systemic effects.
DNEL : 2.08 mg/kg body weight/day

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 1.66 mg/kg body weight/day

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 7.24 mg of substance/m3

Predicted no effect concentration (PNEC):**DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE (CAS: 75980-60-8)**

Environmental compartment: Soil.
PNEC : 0.0557 mg/kg

Environmental compartment: Fresh water.
PNEC : 0.00353 mg/l

Environmental compartment: Sea water.
PNEC : 0.000353 mg/l

Environmental compartment: Intermittent waste water.
PNEC : 0.0353 mg/l

Environmental compartment: Fresh water sediment.

PRIMAIRE D'ADHESION UV - WHITE, POUR MARQUAGE A CHAUD - UVART5000W

PNEC :	0.29 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.029 mg/kg
2-HYDROXY-2-METHYLPROPIOPHENONE (CAS: 7473-98-5)	
Environmental compartment: PNEC :	Soil. 0.000674 mg/kg
Environmental compartment: PNEC :	Fresh water. 0.00195 mg/l
Environmental compartment: PNEC :	Sea water. 0.000195 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 0.0195 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 0.00514 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.000514 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 45 mg/l
DIOXYDE DE TITANE (CAS: 13463-67-7)	
Environmental compartment: PNEC :	Soil. 100 mg/kg
Environmental compartment: PNEC :	Fresh water. 0.184 mg/l
Environmental compartment: PNEC :	Sea water. 0.0184 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 0.193 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 1000 mg/kg
Environmental compartment: PNEC :	Marine sediment. 100 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 100 mg/l
HEXAMETHYLENE DIACRYLATE (CAS: 13048-33-4)	
Environmental compartment: PNEC :	Soil. 0.00397 mg/kg
Environmental compartment: PNEC :	Fresh water. 0.0015 mg/l
Environmental compartment: PNEC :	Sea water. 0.00015 mg/l
Environmental compartment:	Fresh water sediment.

PRIMAIRE D'ADHESION UV - WHITE, POUR MARQUAGE A CHAUD - UVART5000W

PNEC :	0.0243 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.00243 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 2.7 mg/l

8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****General information :**

Physical state : Viscous liquid.

Important health, safety and environmental information

pH : Not stated.

Neutral.

Boiling point/boiling range : Not specified.

Flash Point Interval : FP > 100°C.

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

Density : > 1

PRIMAIRE D'ADHESION UV - WHITE, POUR MARQUAGE A CHAUD - UVART5000W

Water solubility :	Insoluble.
Melting point/melting range :	Not specified.
Self-ignition temperature :	Not specified.
Decomposition point/decomposition range :	Not specified.

9.2. Other information

VOC (g/l) :	1.28
-------------	------

SECTION 10 : STABILITY AND REACTIVITY**10.1. Reactivity**

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

May cause an allergic reaction by skin contact.

11.1.1. Substances**Acute toxicity :**

DIPHENYL(2,4,6-TRIMETHYLBENZOYL)PHOSPHINE OXIDE (CAS: 75980-60-8)

Oral route : LD₅₀ > 5000 mg/kg
Species : Rat (recommended by the CLP)

HEXAMETHYLENE DIACRYLATE (CAS: 13048-33-4)

Oral route : LD₅₀ > 5000 mg/kg
Species : Rat

Dermal route : LD₅₀ = 3650 mg/kg
Species : Rabbit

11.1.2. Mixture

No toxicological data available for the mixture.

PRIMAIRE D'ADHESION UV - WHITE, POUR MARQUAGE A CHAUD - UVART5000W**SECTION 12 : ECOLOGICAL INFORMATION**

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity**12.1.1. Substances**

HEXAMETHYLENE DIACRYLATE (CAS: 13048-33-4)

Fish toxicity : LC50 = 0.38 mg/l
Factor M = 1
Species : *Oryzias latipes*
Duration of exposure : 96 h
OECD Guideline 203 (Fish, Acute Toxicity Test)

NOEC = 0.0723 mg/l
Species : *Oryzias latipes*
Duration of exposure : 35 days
OECD Guideline 210 (Fish, Early-Life Stage Toxicity Test)

Crustacean toxicity : EC50 = 2.7 mg/l
Species : *Daphnia magna*
Duration of exposure : 48 h
OECD Guideline 202 (*Daphnia* sp. Acute Immobilisation Test)

NOEC = 0.14 mg/l
Species : *Daphnia magna*
Duration of exposure : 21 days
OECD Guideline 211 (*Daphnia magna* Reproduction Test)

Algae toxicity : ECr50 = 2.33 mg/l
Species : *Scenedesmus subspicatus*
Duration of exposure : 72 h
OECD Guideline 201 (Alga, Growth Inhibition Test)

NOEC = 0.9 mg/l
Species : *Scenedesmus subspicatus*
OECD Guideline 201 (Alga, Growth Inhibition Test)

Aquatic plant toxicity : Duration of exposure : 72 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability**12.2.1. Substances**

HEXAMETHYLENE DIACRYLATE (CAS: 13048-33-4)

Biodegradability : Rapidly degradable.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

PRIMAIRE D'ADHESION UV - WHITE, POUR MARQUAGE A CHAUD - UVART5000W

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number

-

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

-

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/1480 (ATP 13)

- Container information:

No data available.

- Particular provisions :

No data available.

15.2. Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still to be received

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

I> Indicates changes from previous version

Wording of the phrases mentioned in section 3 :

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

PRIMAIRE D'ADHESION UV - WHITE, POUR MARQUAGE A CHAUD - UVART5000W

H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

CMR: Carcinogenic, mutagenic or reprotoxic.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.